

NEXSTA™

HIGH VENTILATION WINDOW

YKK
ap®


*HEALTHIER HOME
WITH BETTER VENTILATION*





ENHANCE VENTILATION, CREATE WELLNESS AT YOUR HOME

Through YKK AP's research and development¹, we ensure that the high ventilation window provides optimum benefits to our customer. The operable window at high position can increase the ventilation performance by up to three times higher if compared with non-operable one.

Outdoor wind speed²: 2 m/s



Outdoor wind speed²: 2 m/s



Upper : NEXSTA Fixed Window W2400 x H 1400
Lower : NEXSTA Double Top Hung W1600 x H 1500

Upper : NEXSTA Fixed Window W2400 x H 900, combined with NEXSTA High Ventilation Window W 2400 x H 500.
Lower : NEXSTA Double Top Hung W1600 x H 1500

Air Change Rate³

0.37 times/hour

Air Change Rate³

1.66 times/hour

▲ 345%



The airflow moving slowly, even almost not moving at all



Faster airflow helps to cool the indoor space as well as the occupants, thus improves the thermal comfort.




Less air changing makes the room air saturated, cannot push viruses and bacterias away from the room.



The increased air change rate bringing more air fresh inside and push away pollutants and dirty air from the room

VARIOUS APPLICATIONS OF HIGH VENTILATION WINDOW IN YOUR BUILDING

In study room (for privacy)



In bedroom (for privacy)



Provide daylight in stair space



Improve air quality




※ notes :

1. The performance verification for NEXSTA High Ventilation Window was supported by YKK AP R&D Center (Indonesia).
2. Outdoor wind speed of 2 m/s represents the average wind speed during the daytime in most cities in Indonesia.
3. Air change rate or ventilation rate, is a measure of the number of air changes that occur within one hour in a room.

EASIER TO OPERATE AND SAFER FOR YOUR LOVABLE ONES WITH OUR SPECIAL PARTS

PRODUCT VARIATION :

I. Loopless Chain Type



The high position window makes your room more spacious and brighter.




A common high-position window is difficult to open or close due to its unreachable position. The loopless chain system provides easier and safer window operation



Adjustable wire length up to 3.5m

II. Operator Handle Type




Easy And Safe

Even in the hard to reach places the operation is easy




Easy to Operate

The direction of rotation differs depending on the opening



Safe For Kids

It is safe for children, no helper needed



Free From Insect (Optional)


The window can be opened and closed without opening the attached insect screen




Easy to Operate

It is easy for children to operate

PRODUCT DRAWING



Scale 1:4



Scale 1:4



PT YKK AP INDONESIA

Head Office & Factory

Kawasan Industri Manis
 Jl. Manis Raya No.23, Ds. Kadu, Kec. Curug
 Tangerang 15810, Banten, Indonesia
 Tel: +62 21 591 9073
 Fax: +62 21 591 9074
 www.ykkap.co.id

Representative Office in Vietnam

11th Floor AB Tower, 76 Le Lai Street
 Ben Thanh Ward, District 1
 Ho Chi Minh City, Vietnam
 Tel: +84 8 3822 8900
 Fax: +84 8 3822 8901
 www.ykkap.com.vn

Jakarta Sales & Marketing Office

Panin Dai-ichi Life
 Jl. S. Parman Kav.91,3A Floor
 Jakarta 11420, Indonesia
 Tel: +62 21 569 56333 (Hunting)
 Fax: +62 21 569 56335

YKK AP (THAILAND) CO., LTD.

Wave Place Building, 13th Floor No. 55
 Wireless Road, Lumpini, Pathumwan
 Bangkok 10330, Thailand
 Tel: +66 2 655 6334
 Fax: +66 2 655 6399
 www.ykkap.co.th

Surabaya Branch Office

Gedung Bumi Mandiri Tower 1, 6th Floor
 Jl. Jend. Basuki Rachmat 129-137
 Surabaya 60271, Jawa Timur, Indonesia
 Tel: +62 31 535 1800 (Hunting)
 Fax: +62 31 535 1700



www.ykkap.co.id



ykkap_official

ISSUE DATE JUNE , 2021
 PRINTED IN INDONESIA

B0010-21JI-E-1